

UEVE 10W Series

Home Electronics and Appliances AC/DC Adaptor **Standard Product**



UEVEU3010


























(-}#

- Short Circuit Protection
- Over Voltage Protection
- Over Current Protection
- Over Temperature Protection

Safety Standard

- **1**310
- PSE 別表第八 100V-240V 基準に準拠

Product Highlights

- Stability
- Energy and High Efficiency
- Compact Design
- Suitable for home appliances
- Suitable for equipment which meet 60335

Efficiency

- Energy Efficiency Level VI (ErP / DoE)
- Meet Commission Regulation(EU) 2019/1782
- Meet DOE 10 CFR part 429 and 430

Emissions

- FCC
 - ■FCC Part15-B
- CF
- EN(CISPR)55014-B
- VCCI-B

Immunity

■ EN55014-2

The above specifications include the following test standards

- ✓ EN61000-4-2
- ✓ EN61000-4-3
- ✓ EN61000-4-4
- ✓ EN61000-4-5
- ✓ EN61000-4-6
- ✓ EN61000-4-11



Electrical Spec

Input								
Description	Min.	Тур.	Max.	Units	Comment			
Voltage	90	100~240	264	Vac				
Frequency	47	50/60	63	Hz				

Environmental								
Description	Min.	Тур.	Max.	Units	Comment			
Operating Temperature	0	-	40	°C	Free Convection, Sea Level			
Storage Temperature	-20	-	65	°C	Free Convection,Sea Level			
Operating Humidity	5	-	95	%RH	No Condensing			
Storage Humidity	5	-	95	%RH	No Condensing			

Typical model list

Model Name	DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noise	Average Active Efficiency	No-Load Power Consumption	Option / Remark
UEVEU3010-100010SA	10.0V	1.0A	±5%	180mV	180mV	81.95%	0.1W	

- Measurement Condition
- 1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.
- 2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical Spec

